

## This course covers Cortex-A7 ARM CPU

### OBJECTIVES

- This course is split into 3 important parts:
  - Cortex-A7(MP) architecture
  - Cortex-A7(MP) software implementation and debug
  - Cortex-A7(MP) hardware implementation.
- Introduction to Hypervisor new privilege mode is done at the beginning of this course.
- The consequences on address translation is then explained, introducing the 2-stage translation.
- Decoupling guest OS from hardware using traps to Hypervisor is studied.
- The course also details the new features of the Generic Interrupt Controller v2, explaining how physical interrupt requests can be virtualized.
- The course details the new approach regarding integrated timers / counters.
- AXI v4 new capabilities are highlighted with regard to AXI v3.
- Through sequences involving a Cortex-A15MP and a Cortex-A7MP, the hardware coherency is studied, explaining how snoop requests can be forwarded by CCI-400 interconnect.
- Implementation of I/O MMU-400 is also covered.

*A more detailed course description is available on request at [formation@ac6-formation.com](mailto:formation@ac6-formation.com)*

### PREREQUISITES AND RELATED COURSES

- More than 12 correct answers to Cortex-A prerequisites questionnaire.
- Related courses:
  - Programming with RVDS IDE, reference cours [RV0 - Programming with RVDS IDE](#)
  - VFP programming, reference cours [RC0 - VFP programming](#)
  - NEON programming, reference cours [RC1 - NEON-v7 programming](#)

### Environnement du cours

- Cours théorique
  - Support de cours au format PDF (en anglais) et une version imprimée lors des sessions en présentiel
  - Cours dispensé via le système de visioconférence Teams (si à distance)
  - Le formateur répond aux questions des stagiaires en direct pendant la formation et fournit une assistance technique et pédagogique
- Au début de chaque demi-journée une période est réservée à une interaction avec les stagiaires pour s'assurer que le cours répond à leurs attentes et l'adapter si nécessaire

### Audience visée

- Tout ingénieur ou technicien en systèmes embarqués possédant les prérequis ci-dessus.

### Modalités d'évaluation

- Les prérequis indiqués ci-dessus sont évalués avant la formation par l'encadrement technique du stagiaire dans son entreprise, ou par le stagiaire lui-même dans le cas exceptionnel d'un stagiaire individuel.

- Les progrès des stagiaires sont évalués par des quizz proposés en fin des sections pour vérifier que les stagiaires ont assimilé les points présentés
- En fin de formation, une attestation et un certificat attestant que le stagiaire a suivi le cours avec succès.
  - En cas de problème dû à un manque de prérequis de la part du stagiaire, constaté lors de la formation, une formation différente ou complémentaire lui est proposée, en général pour conforter ses prérequis, en accord avec son responsable en entreprise le cas échéant.

## Plan

### First day

#### **OVERVIEW OF CORTEX-A7MP**

- Cortex-A7 architecture
- Organization of a SoC based on Cortex-A7MP
- AMBA4 coherent interconnect capabilities
- I/O MMU
- 64-Byte cacheline size, integrated L2 cache
- VFPv4 and SIMDv2
- Supported instruction sets
- Highlighting differences between Cortex-A9 and Cortex-A7

#### **INSTRUCTION PIPELINE**

- Global organization, dual issue capability
- Fetch / decode / issue / writeback stages
- Data processing unit
- Branch accelerators

#### **INTRODUCTION TO HYPERVISOR STATE**

- Processor privilege levels state machine, user, guest OS, hypervisor
- Detailing the various operation modes (Bare-Metal, Hypervisor kernel and user task, Hypervisor with Guest partition)
- Objective of the Hypervisor
- Support for interrupt nesting in Hypervisor mode
- Detecting VFP/Neon utilization by a Guest partition

#### **EXCEPTION MECHANISM**

- Hypervisor vector table
- Utilization of Vector #5 to trap Guest partition events
- Virtual Interrupt and Abort bits control, IRQ, FIQ, external abort routing control
- Taking exceptions into Hypervisor mode

#### **GENERIC INTERRUPT CONTROLLER (GICv2)**

- Integration in a SoC based on Cortex-A15MP and Cortex-A7MP
- Highlighting the new features with regard to Cortex-A9MP
- Steering interrupts to guest OS or Hypervisor
- Virtual CPU interface
- Split EOI functionality
- Deactivating an interrupt source from the Virtual CPU interface

### Second day

## **VIRTUALIZATION EXTENSIONS**

- New Intermediate Physical Address, 2-stage address translation
- Memory translation system
- Memory management when running in hypervisor mode
- Exposing the MMU to Other Masters, IO MMU
- Emulation support, trapping load and store and executing them in Hypervisor state
- Additional security facilities

## **LARGE PHYSICAL ADDRESS EXTENSIONS SPECIFICATION (LPAE)**

- New 3-level system
- Hypervisor-level address translation
- Level-1 table descriptor format
- Level-2 table descriptor format
- Attribute and Permission fields in the translation tables
- Handling of the ASID in the LPAE
- New cache and TLB maintenance operations

## **MMU IMPLEMENTATION**

- TLB organization, L1-TLB, L2-TLB
- Coherent table walk
- Tablewalk cache and IPA cache operation
- Determining the exact cause of aborts through status registers
- Behavior when MMU is disabled
- TLB maintenance operations

## **OS SUPPORT SYNCHRONIZATION OVERVIEW**

- Inter-Processor Interrupts
- Barriers
- Cluster ID
- Exclusive access monitor, implementing Boolean semaphores
- Global monitor
- Spin-lock implementation
- Using events

## **Third day**

## **LEVEL ONE SUBSYSTEM**

- Cache organization, 2-way instruction cache, 4-way data cache
- Speculative accesses
- Hit Under Miss, Miss under Miss
- Read allocate mode
- Uploading the contents of L1 caches through dedicated CP15 registers
- MOESI data cacheline states
- Detailing cache maintenance operations

## **LEVEL TWO SUBSYSTEM**

- Optional L2 Cache
- Read allocate mode
- ACE master interface
- By means of sequences involving a multi-core Cortex-A7 and external masters, understanding how snoop requests can be used to maintain coherency of data between caches and memory
- Synchronization primitives, the 3 levels of monitors

## GENERIC TIMER

- ARM generic 64-bit timers for each processor
- Virtual time vs Physical time
- Event stream purpose
- Kernel event stream generation
- Hypervisor event stream generation

## PERFORMANCE MONITORING VIRTUALIZATION EXTENSIONS

- Hypervisor performance monitoring
- Guest OS performance monitoring
- Reducing the number of counters available to a Guest OS
- Fully virtualizing the PMU identity registers

## Fourth day

## AMBA4

- AXI-4
- AXI-4 stream protocol
- AXI-4 lite
- AXI Coherency Extension (ACE)
- Exported barriers

## HARDWARE IMPLEMENTATION

- Clock domains
- Resets, power-on reset timing diagram
- Power domains
- Power-on reset sequence, soft reset sequence
- Power management, WFI / WFE, dormant mode based on L2 memory
- Interface to the Power Management Unit
- Powering down a CPU
- External debug over power down

## CCI-400 CACHE COHERENT INTERCONNECT

- AMBA 4 snoop request transport
- Snoop connectivity and control
- ACE master interface
- Connecting 2 CPUs through CCI, managing coherency domains
- Example of Cortex-A7 dual core and Cortex-A15 dual core

## CORESIGHT DEBUG

- Program Trace Macrocell
- Cross Trigger Interface and Cross Trigger Matrix for multi-processor debugging
- Adding Virtual Machine ID in the criterion used to set a breakpoint / watchpoint

## Renseignements pratiques

**Renseignements : 4 jours**